



## DATENBLATT | datasheet

### Stationäres Lesegerät | Stationary Reader

ARE i5 MTX, ARE i5 MTPX, ARE i5 MTL

#### Elektrische Daten | electrical characteristics

Lesesystem   reading systems	ISO FDX-B, ISO hdx, ASK r/o , PSK 1, TROVAN
Betriebsfrequenz   operational frequency	134.2 kHz
Schnittstelle   interface	RS 232
Software   software	AEG ID PC Software
Stromversorgung   power supply	12V, 24V (opt.)
Multiplexer	MTPX Version – 4 channel
Integrierte Antenne   integrated antenna	MTL version
Externa Antenne   external antenna	Geeignet für   suitable for : AAN PT8

#### Umweltbedingungen | environment

Lagertemperatur   storage temperature	-20°C bis   up to +70°C
Betriebstemperatur   operating temperature	0°C bis   up to +50°C
Gehäuse Schutzklasse   packaging protection class	IP 65
Schock&Vibration   Shock&Vibration	IEC 68-2-6 / 29

#### Abmessungen | dimension

Gewicht   weight	Ca. 1800 g
Länge   length	220 mm
Breite   width	122 mm
Höhe   height	80 mm
Material   material	Aluminium Spritzguss   Aluminium Die Cast



**AEG Identifikationssysteme GmbH**

Hörvelsinger Weg 47, D-89081 Ulm | P: +49 (0)731 140088-0 | F: +49 (0)731 140088-9000

E-Mail: [info@aegid.de](mailto:info@aegid.de) | [www.aegid.de](http://www.aegid.de)

AEG is a registered trademark used under license from AB Electrolux (publ).